



Test pressure: **15 BAR**
 Max. working pressure: **10 BAR**
 Max working temperature: **120° C**
 All steel construction: **1.5mm header thickness**
dia 25mm x 1.25mm tubes
 Connections: **½ inch BSP underside tappings**

All dimensions shown are in millimetres

Heat output determined in accordance with EN 442

Manufactured for Bisque by Zehnder of Germany

Model	Output ΔT=50K Watts	Output ΔT=60K Watts	n	Water Content litres	Weight kg	Height ± 2mm	Length ± 2%	Tapping Centres ± 2mm	Fixing Centres ± 2mm
2W-75-37	440	553	1.25	5.6	10	742	398	326	184
2W-75-46	550	691	1.25	7.0	12	742	490	418	276
2W-75-55	660	829	1.25	8.4	14	742	582	510	368
2W-75-64	770	967	1.25	9.8	17	742	674	602	460
2W-120-37	662	832	1.25	8.8	15	1192	398	326	184
2W-120-46	827	1041	1.25	11.0	19	1192	490	418	276
2W-120-55	992	1249	1.25	13.2	23	1192	582	510	368
2W-120-64	1158	1457	1.25	15.4	27	1192	674	602	460
2W-150-28	624	788	1.28	7.8	14	1492	306	234	92
2W-150-37	832	1051	1.28	10.4	18	1492	398	326	184
2W-150-46	1040	1313	1.28	13.0	23	1492	490	418	276
2W-150-55	1248	1576	1.28	15.6	28	1492	582	510	368
2W-180-28	744	945	1.31	9.0	16	1792	306	234	92
2W-180-37	992	1260	1.31	12.0	22	1792	398	326	184
2W-180-46	1240	1575	1.31	15.0	27	1792	490	418	276
2W-180-55	1488	1889	1.31	18.0	32	1792	582	510	368