



All dimensions shown are in millimetres

All stainless steel construction: **30mm x 50mm x 1.2mm tubes**  
**30mm x 30mm x 1mm headers**

Connections: **1.2m long flying lead (3 core)**

Immersion heater rating: **IPX4**

Model	Output Watts	Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 5mm
ALBE_-100-50/F	200	13	1000	500	760
ALBE_-140-50/F	250	18	1380	500	1140
ALBE_-180-50/F	300	22	1760	500	1520

## Tools & Material Required

Tape measure  
 Screwdriver - crosshead  
 Screwdriver - flathead  
 Electric drill  
 Masonry drill bit - 8mm diameter  
 Spirit level  
 Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug	4
B	Bracket	4
C	Screw - Rnd Head, 6mm dia x 50mm	4
D	Grub Screw	4
E	Allen Key	1

## Assembly Instructions

Accurately mark out bracket holes on wall using spirit level.  
 Drill four 8mm diameter holes to a minimum depth of 60mm & insert wall plugs (A).  
 Screw brackets (B) into wall plugs (A) with 6mm diameter x 50mm screws (C).  
 Slide boss on radiator into bracket (B) and secure in position by tightening grub screw (D) with allen key (E).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

*Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.*

