



All dimensions shown are in millimetres

All steel construction: **dia 23mm x 1mm tubes**
30x40mm D-shaped headers

Connections: **1.2m long flying lead (3 core)**

Immersion heater rating: **IPX4 or better**

Manufactured for Bisque by Zehnder

Model	Output Watts	Chrome Finish		Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 2mm
		Output Watts	Output Watts				
DELE-80-50/F	400	200	200	10	786	500	640
DELE-120-50/F	500	400	400	15	1226	500	1080
DELE-180-50/F	600	500	500	23	1866	500	1720
DELE-80-60/F	400	200	200	11	786	600	640
DELE-120-60/F	600	400	400	17	1226	600	1080
DELE-180-60/F	600	600	600	26	1866	600	1720

Tools & Material Required

- Tape measure
- Screwdriver - crosshead
- Pliers
- Electric drill
- Masonry drill bit
- Spirit level
- Stepladder (for taller radiators)

Key	Component	Qty
A	Boss	4
B	Wall Plug	4
C	Bracket	4
D	Screw, 6mm dia x 50mm	4
E	Washer	4
F	Grub Screw	4
G	Allen Key	1

Assembly Instructions

- Screw bosses (A) to studs on the back of the radiator.
- Accurately mark out bracket holes on wall using spirit level, to dimensions as shown on Technical Data Sheet.
- Drill four holes to a minimum depth of 65mm & insert wall plugs (B).
- Attach brackets (C) to wall with screws (D) & washers (E).
- Hang radiator onto wall by inserting bosses (A) into brackets (C).
- Tighten grub screws (F) with Allen key (G).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.

